UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/709,344	04/29/2004	Georg Reinbold	P7482US	3343
30008 7590 02/23/2007 GUDRUN E. HUCKETT DRAUDT			EXAMINER	
LONSSTR. 59			LEE, LAURA MICHELLE	
WUPPERTAL, 42289 GERMANY			ART UNIT	PAPER NUMBER
ODIUM II VI			3724	
				<u> </u>
SHORTENED STATUTOR	RY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MONTHS 02/23/2007		PAPER .		

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

<u> </u>		Application No.	Applicant(s)
Office Action Summary		10/709,344 REINBOLD ET AL.	
		Examiner	Art Unit
		Laura M. Lee	3724
Period fo	The MAILING DATE of this communication apports Reply	ears on the cover sheet with the o	orrespondence address
WHIC - Exte after - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DANSIONS of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. Operiod for reply is specified above, the maximum statutory period we are to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing ed patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tire will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	nely filed the mailing date of this communication. ED (35 U.S.C. § 133).
Status			
,	Responsive to communication(s) filed on <u>30 North</u> This action is FINAL . 2b) This Since this application is in condition for alloward closed in accordance with the practice under E	action is non-final. nce except for formal matters, pro-	
Disposit	ion of Claims		·
5)□ 6)⊠ 7)□ 8)□ Applicat	Claim(s) 1 and 3-14 is/are pending in the application of the above claim(s) is/are withdraw Claim(s) is/are allowed. Claim(s) 1, 3-14 is/are rejected. Claim(s) is/are objected to. Claim(s) are subject to restriction and/or are subject to restriction and/or is/are objected to by the Examiner The drawing(s) filed on is/are: a) access Applicant may not request that any objection to the organization is objected to by the Examiner and access and access are also access and access and access are also access and access access and access are also access and access are also access and access access and access access and access are also access and access access and access access and access access access and access access access and access access access and access acces	r. epted or b) □ objected to by the	
11)	Replacement drawing sheet(s) including the correction. The oath or declaration is objected to by the Experience.	on is required if the drawing(s) is ob	jected to. See 37 CFR 1.121(d).
Priority ι	ınder 35 U.S.C. § 119		
12)⊠ a)	Acknowledgment is made of a claim for foreign All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau See the attached detailed Office action for a list of	s have been received. s have been received in Applicati ity documents have been receive (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachmen		Λ. Γ. 1	(DTO 442)
2) 🔲 Notic 3) 🔯 Infon	te of References Cited (PTO-892) te of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO/SB/08) tr No(s)/Mail Date 1/13/2005; 12/01/2006.	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal F 6) Other:	ate

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed have been fully considered but they are not persuasive. In regards to the applicant's arguments to claim 1, see the current rejection of Murray '937 in view of Murray '603. In regards to claim applicant's arguments that the 35 USC 103 rejection of Murray in view of Bolton et al. does not teach that the control unit does not continuously recalculate the feeding velocity, it is noted that recalculation is inherently present in the Bolton teaching. As the Bolton reference teaches a monitoring of the conveyor by the encoder, there is an inherent understanding of a continuous monitoring of a change in conveyor distance over time period. The continuous monitoring results in multiple readings of a change in distance over time, which corresponds to a monitoring of a change in velocity or in other words, a recalculation of the velocity. Additionally, Bolton teaches that there are a set of scanners, 40,42 such that detection of an off size defect by the scanners is conveyed to the computer, so that the computer keeps track of the position of the defect as it moves along the conveyor. Therefore, the encoder 50 continuously monitors (recalculates) the position and therefore, velocity, of the wood along the conveyor.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

Art Unit: 3724

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1,3 and 6-12 are rejected under 35 U.S.C. 102(b) as being anticipated by Murray (U.S. Publication 2002/0069937) or, in the alternative, under 35 U.S.C. 103(a) as obvious over Murray (U.S. Patent 6,308,603).

In regards to claims 1 and 13, Murray '937 discloses (see Figure 5) a method for sawing pieces of wood in a sawing station, the method comprising the steps of:

- a) measuring the pieces of wood in a measuring station (parallel log scanners, 56,57; paragraph [0053];);
- b) sequentially transporting (conveyors 60,62) the pieces of wood from the measuring station to a sawing station (log indexer 58 /buck sawing apparatus, 10);

It is also noted that the limitation "sawing station" has been interpreted to not be limited to include only the structure holding the sawing blade, such that the indexing system is also a part of the sawing station. Additionally, if the sawing station had not been recited as being a part from the measuring station, the limitation could have been interpreted to mean the entire wood processing operation as shown in Figure 5.

c) cutting the pieces of wood in the sawing station into at least two sections based on measured results taken in step a)(paragraph [0038]; The log 12 will have been scanned prior to arrival at the tilted infeed conveyor 14 and this scanning information is used to determine the location of the cuts made by cut-off saw 26.);

Art Unit: 3724

wherein the step b) a second piece of wood that trails (off of log deck, 50) immediately a first piece of wood being cut (by saw, 26) in the sawing station is already transported into the sawing station (log indexer 58) while the first piece of wood is still being cut (paragraph [0041]) where in the step b) a feeding velocity of the second piece of wood is controlled by a control unit (the feeding of the wood is controlled by a variable speed drive, that inherently has a control unit; whether manual or automatic to adjust the speed and a log indexer 58) such that the second piece of wood does not contact the first piece of wood within the sawing station (the wood pieces never touch as evidenced by paragraph [0044]; As illustrated in FIG. 5, logs are transported transversely on a log deck 50 to a diverter gate 52 where they are diverted onto one of two parallel conveyors 54, 55 which transport the logs longitudinally through two parallel log scanners 56, 57 and from there by parallel conveyors 60, 62 to a log indexer 58 where two log sweeps 59 alternately sweep the logs onto in feed conveyor 14 and from there to the buck sawing apparatus 10);

and a spacing of an end face of the second piece of wood relative to a trailing end face of the first piece of wood is minimized (paragraph [0041] Since the infeed and outfeed conveyors continue to feed during the intervals when rolls 18, 19, 20, and 21 are stopped to buck the log, gaps between the logs are reduced and the throughput is increased).

However, to the extent that it can be argued that the second piece of wood that trails a the first piece of wood would not be located in the log indexer portion (58) of the sawing station while the first piece of wood is still being cut, attention is directed to the

Art Unit: 3724

Murray '603 reference. Murray '603 discloses that in conventional systems, where the logs are conveyed on a single conveyor, through the scanners, that a gap of two to four feet between consecutive logs is well-known, yet undesirable (column 5, lines 14-34). Therefore, as similarly disclosed by Murray '937 (paragraph [0044]), it is desirable to divert the logs through two scanners to reduce gaps between logs as they enter the bucking system. Although neither Murray reference discloses what this ideal gap would be, the worst scenario would be a gap of four feet as is already old and well known in the art. Additionally, as a perspective of the size of the sawing system, Murray '603 discloses that the feed rolls have a diameter of about two feet. As the identical feed rollers are disclosed in Murray '603 and Murray '937 (see Figure 1 of each reference), and identical diverting systems (see Figure 5 of each reference) it can be extrapolated that even if the gap was at a worst case of four feet, the second piece of wood would be well within the indexing area, when the first piece of wood was being cut. It would have been obvious to one having ordinary skill in the art at the time of the invention that the second piece of wood of the Murray '937 device would have been within the sawing station (at the indexing point) while the first piece of wood was being cut since as taught by the Murray '603 device, a gap of four feet is undesirable, which dimensionally would place the second piece of wood well within the indexing station.

In regards to claim 3, Murray '937 as modified by Murray '603, discloses wherein, in the step of controlling, the feeding velocity of the second piece of wood is controlled variable (variable-feed drive).

Art Unit: 3724

In regards to claim 6, Murray '937 as modified by Murray '603, discloses wherein a feeding velocity of the second piece of wood is controlled so as to minimize between the first and second pieces of wood (paragraphs [0038] and [0041].

In regards to claim 7, Murray '937 as modified by Murray '603, discloses wherein, in the step a), a length of the pieces of the wood is measured (paragraph [0038]). The log is first scanned with log scanners 56,57

In regards to claim 8, Murray '937 as modified by Murray '603, discloses wherein a defect of the pieces of wood is measured. As the log is first scanned with log scanners 56,57, and defects of the wood are also scanned.

In regards to claim 9, Murray '937 as modified by Murray '603, discloses comprising step of saving the measured results (as they are transferred to the cut-off saw).

In regards to claim 10, Murray '937 as modified by Murray '603, discloses the step of controlling the feeding velocity of the second piece of wood, wherein the measured results that are saved are used for controlling the feeding velocity.

In regards to claim 11, Murray '937 as modified by Murray '603, discloses in the step b) the second pieces of wood are supplied without interruption to the sawing station (paragraph [0041]).

In regards to claim 12, Murray '937 as modified by Murray '603, discloses the step of decoupling a drive for transporting the pieces of wood to the sawing station from a drive of the sawing station (paragraph [0048], as the log is transferred from the conveyor to the hourglass roll).

Application/Control Number: 10/709,344 Page 7

Art Unit: 3724

Claim Rejections - 35 USC § 103

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 4 and 5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Murray in view of Bolton et al. (U.S. Patent 4,934,228), herein referred to as Bolton. Murray discloses the claimed invention except the step of continuously monitoring a position of the pieces of wood, wherein the control unit calculates the feeding velocity based upon the continuously monitored positions of the pieces of wood. However, attention is directed to the Bolton device that discloses a system of diverting veneer sheets having off size defects. The system includes a set of scanners, 40,42 such that detection of an off size defect by the scanners is conveyed to the computer, so that the computer keeps track of the position of the defect as it moves along the conveyor 36. The movement of the in-feed conveyor is tracked by an encoder 50 connected positioned at the end of the in-feed conveyor 36. Whereas the conveyor may be simply driven at a desired speed and that speed input to the computer 38, it is preferable to use the encoder 50, which monitors the conveyor movement. Therefore, the encoder 50 continuously monitors the pieces of wood, where their defect position is relayed to the computer (controller), and where the conveyor's speed is variable based upon the

Art Unit: 3724

wood's position. It would have been obvious to modify the variable speed conveying means of Murray in view of the teachings of Bolton as a function of continuous monitoring of the positions of the wood's defects in order to control the cutting and removal of the defects.

6. Claims 13 and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Murray (U.S. Patent 6,308,603) in view of Wurster and Dietz (DE4327040).

Murray discloses a method for sawing pieces of wood in a sawing station, the method comprising the steps of:

- a) measuring the pieces of wood in a measuring station (column 3, lines 6-8);
- b) sequentially transporting the pieces of wood from the measuring station to a sawing station (along infeed conveyor 14; Figure 1);

It is also noted that the limitation "sawing station" has been interpreted to not be limited to include only the structure holding the sawing blade, such that the conveying system is also a part of the sawing station.

c) cutting the pieces of wood in the sawing station into at least two sections based upon the measured results taken in step a)(column 3, lines 6-8);

wherein in the step b) a second piece of wood that trails immediately a first piece of wood being cut in the sawing station is already transported into the sawing station while the first piece of wood is still being cut; (*Murray discloses that when the logs are conveyed on a single conveyor, through the scanners, that a gap of two to four feet between consecutive logs is well-known, yet undesirable (column 5, lines 14-34). As a*

Art Unit: 3724

perspective of the size of the sawing system, Murray further discloses that the feed rolls have a diameter of about two feet, and as shown in Figures 1-4, and it can be extrapolated that even if the gap was at a worst case of four feet, the second piece of wood need to be on the conveyor (14), when the first piece of wood was being cut in order to maintain a minimum of four feet difference between the two wood pieces)

In this embodiment, Murray does not discloses that wherein in the step b) a feeding velocity of the second piece of wood is selected such that the second piece of wood does not contact within the sawing station the first piece of wood and a spacing of an end face of the second piece of wood relative to a trailing end face of the first piece of wood is minimized, and wherein the feeding velocity of the second piece of wood is controlled as a function of a position of the trailing end face of the first piece of wood within the sawing station. However, attention is directed to the Wurster and Dietz device. Wurster and Dietz disclose an apparatus for conveying boards that as disclosed by the provided translation of German reference, a means of utilizing sensors that detect the wood movement in combination with conveyors to adjust the speed of the conveyors/boards so that the boards do not hit the preceding boards. It would have been obvious to one having ordinary skill in the art to have modified the Murray device with a sensing and conveying means as taught by Wurster and Dietz to prevent boards from contacting each other as they move down the conveyors.

Art Unit: 3724

Conclusion

7. Applicant's amendment in combination with applicant's submission of an information disclosure statement under 37 CFR 1.97(c) with the fee set forth in 37 CFR 1.17(p) on 12/01/2006 prompted the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a) and MPEP § 609.04(b). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Laura M. Lee whose telephone number is (571) 272-8339. The examiner can normally be reached on Monday through Friday, 8:00am to 4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Boyer Ashley can be reached on (571) 272-4502. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

LML 2/14/2007

BOYER D. ASHLEY SUPERVISORY PATENT EXAMINER